



# UX 400/UX 401 HIGH-TECH SELF-SERVICE SOLUTION

Contactless transactions are where the world is heading. Depend on the UX 400/UX 401 contactless solution to be ready for NFC-enabled payments, quick-identification confirmation or other contactless transactions at unattended, high-transaction-volume environments, such as on-street parking meters, petroleum pumps and ticketing machines. From mobile wallets to the wave of a card, the UX 400/UX 401 satisfies the need for secure and rapid contactless transactions.



Maximizing  
Security and  
Durability

## OPTIMIZING THE CONSUMER EXPERIENCE

- Anti-vandalism enclosure that can withstand an impact up to 10 Joules
- Weatherproof enclosure provides top-level protection against dust, liquids and other harmful substances, withstanding IP65
- Optical guidance by four LEDs
- System wake-up on card tapping
- Illuminating contactless logo
- Maintenance-free device and outdoor-rugged peripheral wrapped into one sleek, modern design
- No specific software is required on UX 400/UX 401; everything is driven by UX 300/UX 301 master

Outdoor-  
Rugged  
Peripheral



## SPECIFICATIONS

Connectivity	Analog and digital signal UX 400 connects to UX 300 UX 401 connects to UX 301
Contactless	ISO14443 A&B   MiFare   ISO18092 capable   supports major NFC/contactless schemes
Security	PCI PTS 3.X approved   SRED   Meets EMV L1 and L2 requirements when connected to UX 300/UX 301
Environmental	-30° to 70° C (-22° to 158° F) operating temperature   -30° to 70° C (-22° to 158° F) storing temperature   10% to 90% relative humidity, non-condensing
Physical	100mm L x 27mm W x 92mm H (3.94in L x 1.06in W x 3.62in H)
Mechanics (cutout)	73.2mm x 61.2mm (2.88in x 2.41in)